TR 171 - Spécifications techniques

Description

TR 171 est un pneu avec bande de roulement profonde adapté pour les tracteurs dans les travaux de la terre. Grâce à ses extraordinaires propriétés d'auto-nettoyage, ce pneu est idéal pour les terrains humides et mouillés. Développé avec un mélange spécial, TR 171 assure une excellente traction et une grande durabilité même dans les conditions les plus difficiles.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	12.4 - 28
LI/SS	113 A8

Dimensions US Standard

Usa code	94004386
Ply Rating	6
Section Width (inch)	12.4
Overall Diameter (inch)	49.6
Static Loaded Radius (inch)	23.2
Rolling Circumference (inch)	152
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-003556
TRA Code	R1W+

Load capacity (lbs)

mph / psi	24
25	2540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 10:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..