

## TR 171 - Spécifications techniques



### Description

TR 171 est un pneu avec bande de roulement profonde adapté pour les tracteurs dans les travaux de la terre. Grâce à ses extraordinaires propriétés d'auto-nettoyage, ce pneu est idéal pour les terrains humides et mouillés. Développé avec un mélange spécial, TR 171 assure une excellente traction et une grande durabilité même dans les conditions les plus difficiles.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	14.9 - 28
LI/SS	137 A6

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	388
Overall Diameter (mm)	1370
Static Loaded Radius (mm)	636
Rolling Circumference (mm)	4246
SRI (mm)	650
Rim Rec	W 13
Rim Alt	W 11 ; W 12
ECE	E11-106R-004498
TRA Code	R1W+

## Load capacity (Kg)

km/h / bar	2.60
30	2300

Printed on 24/04/2024 16:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..