

## TR 270 - Spécifications techniques



### Description

TR 270 est un pneu pour tracteurs adapté pour les applications de travail de la terre. Ce pneu a été spécialement conçu pour offrir un maximum de performances sur les terrains humides et mouillés. Dans ces conditions de sol, un pneu doit offrir une adhérence supérieure et des propriétés élevées d'auto-nettoyage. TR 270 satisfait parfaitement à ces requêtes.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	18.4 - 30
LI/SS	139 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	465
Overall Diameter (mm)	1580
Static Loaded Radius (mm)	720
Rolling Circumference (mm)	4787
Rim Rec	DW 16 L ; DW 16 A
Rim Alt	W 15 L ; DW 15 A
ECE	E11-106R-003557
TRA Code	R2

## Load capacity (Kg)

km/h / bar	1.40
30	2430

Printed on 26/04/2024 00:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..