

TR 270 - Spécifications techniques



Description

TR 270 est un pneu pour tracteurs adapté pour les applications de travail de la terre. Ce pneu a été spécialement conçu pour offrir un maximum de performances sur les terrains humides et mouillés. Dans ces conditions de sol, un pneu doit offrir une adhérence supérieure et des propriétés élevées d'auto-nettoyage. TR 270 satisfait parfaitement à ces requêtes.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	23.1 - 34
LI/SS	150 A8

Dimensions US Standard

Usa code	94027972
Ply Rating	10
Section Width (inch)	23.2
Overall Diameter (inch)	72.8
Static Loaded Radius (inch)	33.1
Rolling Circumference (inch)	217.8
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-003623
TRA Code	R2

Load capacity (lbs)

mph / psi	20
25	7400

Printed on 25/04/2024 16:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..