

TR 273 - Spécifications techniques



Description

TR 273 est un pneu pour tracteurs adapté per les applications de travail de la terre. Ce pneu a été spécialement conçu pour offrir un maximum de performances sur les terrains humides et mouillés. Dans ces conditions de sol, un pneu doit offrir une adhérence supérieure et des propriétés élevées d'auto-nettoyage. TR 273 satisfait parfaitement à ces requêtes.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	18.4 - 38
LI/SS	152 A6

Dimensions International Standard

Ply Rating	12
TKPH	1
Section Width (mm)	465
Overall Diameter (mm)	1800
Static Loaded Radius (mm)	822
Rolling Circumference (mm)	5579
Rim Rec	W 16
Rim Alt	W 15
ECE	E11-106R-005316
TRA Code	R2

Load capacity (Kg)

km/h / bar	2.30
30	3550

Printed on 26/04/2024 20:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..