

TR 313 - Spécifications techniques



Description

TR 313 est un pneu pour pelouses et jardins adapté pour les services municipaux de voirie et les opérations de travail de la terre avec des outils agricoles, trancheuses et machines pour la récolte dans les vergers. La zone de contact large garantit une excellente adhérence. Le pneu TR 313 a été conçu pour garantir un niveau élevé de stabilité même dans des conditions opérationnelles critiques ainsi que des qualités excellentes de autonettoyage.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Outillage agricole • Tracteur pour vergers •
Trancheuse

Version	STANDARD
Type	TL
Tyre Size	31 X 15.50 - 15

Dimensions US Standard

Usa code	94025589
Ply Rating	8
Section Width (inch)	14.6
Overall Diameter (inch)	30.7
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	87.9
Rim Rec	13 LB
ECE	E4-106R-002208

Load capacity (lbs)

mph / psi	45
30	2760

Printed on 28/11/2023 18:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..