

## TR 315 - Spécifications techniques



### Description

TR 315 est adapté pour les pelouses et les jardins et les opérations de travail de la terre et les services municipaux de voirie. Ce pneu est idéal pour être utilisé avec des outils agricoles, trancheuses et machines pour la récolte dans les vergers. TR 315 bénéficie d'une zone de contact large qui lui confère une excellente adhérence des qualités excellentes de autonettoyage ainsi qu'une stabilité exceptionnelle dans n'importe quelles conditions.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Outillage agricole • Tracteur pour vergers •  
Trancheuse

Version	STANDARD
Type	TL
Tyre Size	23 X 8.50 - 12

## Dimensions US Standard

Usa code	94022335
Ply Rating	4
Section Width (inch)	8.1
Overall Diameter (inch)	22.6
Static Loaded Radius (inch)	10.2
Rolling Circumference (inch)	65.7
Rim Rec	7 JA ; 7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-004518

## Load capacity (lbs)

mph / psi	22
10	1100

Printed on 28/11/2023 15:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..