

TR 315 - Spécifications techniques



Description

TR 315 est adapté pour les pelouses et les jardins et les opérations de travail de la terre et les services municipaux de voirie. Ce pneu est idéal pour être utilisé avec des outils agricoles, trancheuses et machines pour la récolte dans les vergers. TR 315 bénéficie d'une zone de contact large qui lui confère une excellente adhérence des qualités excellentes de autonettoyage ainsi qu'une stabilité exceptionnelle dans n'importe quelles conditions.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Tracteur pour vergers •
Trancheuse

Version	STANDARD
Type	TL
Tyre Size	31 X 15.50 - 15

Dimensions International Standard

Ply Rating	10
Section Width (mm)	390
Overall Diameter (mm)	800
Static Loaded Radius (mm)	354
Rolling Circumference (mm)	2320
Rim Rec	13 LB
ECE	E4-106R-001553

Load capacity (Kg)

km/h / bar	4.10
50	1450

Printed on 26/04/2024 23:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..