

TR 317 - Spécifications techniques



Description

TR 317 est adapté pour les services municipaux de voirie et le travail de la terre avec des outils agricoles des trancheuses et des machines pour la récolte dans les vergers. Le pneu TR 317 bénéficie d'une zone de contact large qui lui confère une excellente adhérence, des qualités excellentes de autonettoyage ainsi qu'une stabilité exceptionnelle dans n'importe quelles conditions.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Tracteur pour vergers •
Trancheuse

| | |
|-----------|---------------|
| Version | HD |
| Type | TL |
| Tyre Size | 18 X 8.50 - 8 |

Dimensions US Standard

| | |
|------------------------------|-------------------------------|
| Usa code | 94045884 |
| Ply Rating | 6 |
| Section Width (inch) | 8.5 |
| Overall Diameter (inch) | 17.7 |
| Static Loaded Radius (inch) | 7.8 |
| Rolling Circumference (inch) | 51.4 |
| Rim Rec | 7.00 I - 55 ; I - 70 ; I - 90 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 34 |
| 10 | 1050 |

Printed on 04/02/2023 14:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..