

TR 318 - Spécifications techniques



Description

TR 318 a été spécialement conçu pour les machines d'irrigation et les outils agricoles. Les pavés à double angle assurent une excellente traction et un confort de conduite extraordinaire. TR 318 bénéficie aussi de formidables qualités d'auto-nettoyage.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Pulvérisateur

Version	STANDARD
Type	TL
Tyre Size	23 X 9.00 - 12
LI/SS	93 A3

Dimensions International Standard

Ply Rating	6
Section Width (mm)	220
Overall Diameter (mm)	585
Rim Rec	7.0
ECE	E11-106R-004521

Load capacity (Kg)

km/h / bar	3.0
15	650

Printed on 24/04/2024 21:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..