

TR 319 - Spécifications techniques



Description

TR 319 est un pneu pour les outils agricoles, tracteurs pour vergers et trancheuses dans les applications de jardinage, les services municipaux de voirie ainsi que pour le travail de la terre. Ce pneu possède une large zone de contact, ce qui se traduit par une excellente traction. C'est pourquoi TR 319 est parfaitement approprié pour des applications sur surfaces mouillées où on a besoins des excellentes qualités de autonettoyage.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Tracteur pour vergers •
Trancheuse

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 29 X 12.50 - 15 |
| LI/SS | 106 B |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94053247 |
| Ply Rating | 8 |
| Section Width (inch) | 12.3 |
| Overall Diameter (inch) | 29.7 |
| Static Loaded Radius (inch) | 14.2 |
| Rolling Circumference (inch) | 89.1 |
| Rim Rec | 10 LB |
| ECE | E11-106R-004605 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 45 |
| 30 | 2090 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/12/2024 10:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..