

## TR 387 - Spécifications techniques



### Description

TR 387 est un pneu agro-industriel, adapté pour les remorques pour canne à sucre et les compacteurs. Ce pneu se distingue de par sa capacité de charge élevée ainsi qu'une plus longue vie du pneu. Il est disponible en différentes versions afin de répondre aux exigences spécifiques des utilisateurs en termes de résistance aux coupures et déchirures, opérations de service pénible et durabilité. La version «dual bead», à double bourrelet, est particulièrement adaptée pour les tracteurs industriels et les opérations de transport avec remorques.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Remorque

Industriel: Compacteur

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26
LI/SS	155 A8

## Dimensions US Standard

Usa code	94005130
Ply Rating	16
Section Width (inch)	23.3
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	184.6
Rim Rec	DW 20 B
TRA Code	R3

## Load capacity (lbs)

mph / psi	34
25	8540

Printed on 26/04/2024 07:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..