

## TR 390 - Spécifications techniques



### Description

TR 390 est un pneu agro-industriel, adapté pour les remorques pour canne à sucre et les compacteurs. Le pneu TR 390 se distingue de par une capacité de charge élevée et une durabilité supérieure. La version « dual bead HD », à double bourrelet HD, est particulièrement adaptée pour les tracteurs industriels et les opérations de transport avec remorques, tandis que la version « dual bead HD special », spéciale à double bourrelet HD, est idéale pour les opérations de service pénible.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Remorque  
Industriel: Compacteur

Version	STANDARD
Type	TL
Tyre Size	23.1 - 26
LI/SS	145 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	595
Overall Diameter (mm)	1560
Static Loaded Radius (mm)	690
Rolling Circumference (mm)	4545
SRI (mm)	750
Rim Rec	DW 20 B
ECE	E11-106R-003595
TRA Code	R3

## Load capacity (Kg)

km/h / bar	1.10
30	2900

Printed on 23/04/2024 11:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..