

## TR 390 - Spécifications techniques



### Description

TR 390 est un pneu agro-industriel, adapté pour les remorques pour canne à sucre et les compacteurs. Le pneu TR 390 se distingue de par une capacité de charge élevée et une durabilité supérieure. La version « dual bead HD », à double bourrelet HD, est particulièrement adaptée pour les tracteurs industriels et les opérations de transport avec remorques, tandis que la version « dual bead HD special », spéciale à double bourrelet HD, est idéale pour les opérations de service pénible.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Remorque  
Industriel: Compacteur

|           |           |
|-----------|-----------|
| Version   | DUAL BEAD |
| Type      | TL        |
| Tyre Size | 28L - 26  |
| LI/SS     | 160 A6    |

## Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Ply Rating                 | 16             |
| Section Width (mm)         | 714            |
| Overall Diameter (mm)      | 1560           |
| Static Loaded Radius (mm)  | 690            |
| Rolling Circumference (mm) | 4545           |
| Rim Rec                    | DW 25 B        |
| Rim Alt                    | DW 23 B        |
| ECE                        | E4-106R-002337 |
| TRA Code                   | R3             |

## Load capacity (Kg)

| km/h / bar | 1.90 |
|------------|------|
| 30         | 4500 |

Printed on 23/04/2024 16:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..