

TR 391 - Spécifications techniques



Description

TR 391 est un pneu agro-industriel, adapté pour les opérations de transport et de compactage avec remorques pour canne à sucre et les compacteurs. TR 391 se distingue de par une capacité de charge élevée ainsi qu'un cycle de vie plus longue.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

Industriel: Compacteur

Version	STANDARD
Type	TL
Tyre Size	14.9 - 24
LI/SS	123 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	405
Overall Diameter (mm)	1270
Static Loaded Radius (mm)	574
Rolling Circumference (mm)	3805
SRI (mm)	600
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 13 L ; DW 12
TRA Code	R3

Load capacity (Kg)

km/h / bar	1.40
30	1550

Printed on 24/02/2024 06:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..