

TR 393 (B) - Fiche de données



Description

Le TR 393 (B) a été spécialement conçu pour les semoirs, les épandeurs et le déploiement de machines sur route et hors route. La conception spéciale de la bande de roulement offre des propriétés de flottaison et d'autonettoyage optimales, ainsi qu'une longue durée de vie. Grâce à sa vaste surface de contact, le TR 393 (B) assure une excellente traction et minimise le compactage du sol.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Épandeur

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
31 X 13.50 - 15	STUBBLE RESISTANT	R3	124 B	12	10 LB		350	777	TL	E11-106R-008131

Printed on 01/05/2024 07:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..