

TR 461 - Spécifications techniques



Description

TR 461 est un pneu BKT conçu per les applications entretien de la voirie avec tracteurs et pour les opérations de chargement avec chargeurs télescopiques. La protection du flanc est caractérisée par une résistance particulière aux coupures et lacérations, ce qui garantit une vie plus longue du pneu même sur des surfaces dures, ainsi qu'une excellente stabilité.

UM

US Standard

Construction

❖ BIAS

Machinery

Industriel: Chargeuse-pelleteuse • Chargeuse télescopique
• Tracteur

Version	HD
Type	TL
Tyre Size	620/60 B 34
LI/SS	175 A8

Dimensions US Standard

Usa code	94067015
Overall Width (inch)	24.2
Overall Diameter (inch)	64.1
Static Loaded Radius (inch)	29.5
Rolling Circumference (inch)	194.1
Rim Rec	DW 20 B
TRA Code	R4

Load capacity (lbs)

mph / psi	58
25	15210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 10:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..