

TR 675 - Spécifications techniques



Description

TR 675 est un pneu radial spécialement conçu pour les applications forestières. Sa conception à barrettes robuste offre de remarquables performances de traction et d'autonettoyage, tandis que la structure solide de la carcasse permet de transporter de lourdes charges et ses ceintures en acier protègent le pneu des crevaisons et autres types de détérioration.

Le TR 675 est doté d'un composé de bande de roulement résistant aux coupures offrant une très bonne résistance aux entailles et aux éclats, même sur des terrains difficiles en conditions extrêmes.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Porteur

Version	STEEL BELTED
Type	TL
Tyre Size	540/65 - 28
LI/SS	155 A8/161 A2

Dimensions International Standard

Ply Rating	16
Section Width (mm)	530
Overall Diameter (mm)	1425
Static Loaded Radius (mm)	663
Rolling Circumference (mm)	4440
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E11-106R-005271
TRA Code	LS2

Load capacity (Kg)

km/h / bar	3.30
40	3875

Printed on 04/03/2024 12:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..