

TR 678 IND - Fiche de données



Description

TR 678 IND a été particulièrement conçu pour les applications industrielles. Le dessin robuste des crampons garantit d'excellentes qualités de traction et autonettoyage. La structure résistante de la carcasse permet une capacité de charge élevée, tandis que les ceintures d'acier protègent le pneu des dommages et crevaisons. TR 678 est caractérisé par un mélange résistant aux coupures qui garantit, même sur des terrains difficiles dans des conditions extrêmes, une excellente résistance aux coupures et lacérations.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Pelleteuse • Remorque

| SIZE | Version | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|---------------|-----------|-------------------|--------------------|----------|---------|-----|------|-----|------|------|-----------------|
| 600/40 - 22.5 | DUAL BEAD | 157 A8 | 169 A8 | AG 20.00 | | 615 | 1085 | 483 | 3264 | TL | E11-106R-006973 |

Printed on 26/04/2024 23:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..