

TR 882 - Spécifications techniques



Description

TR 882 est un pneu polyvalent convenant à de nombreuses applications et machines. Il a été conçu pour les outils agricoles, les machines pour la récolte du foin/presses à paille et les engins pour les plantations de canne à sucre. Développé avec un mélange spécial pour réduire les dommages, ce pneu assure durabilité supérieure et traction excellente dans toutes les conditions dans les champs. TR 882 est aussi disponible dans les versions "aramid-belted", "HD" et "special" pour répondre aux exigences les plus spécifiques des utilisateurs finaux.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Outillage agricole • Remorque
Industriel: Remorque

Version	SPECIAL
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	132 A8
LI/SS FREE ROLLING	145 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	400
Overall Diameter (mm)	875
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2605
SRI (mm)	410
Rim Rec	AG 13.00
ECE	E11-106R-004332

Load capacity (Kg)

km/h / bar	3.60
10 FR	4060
25 FR	3450
30 FR	3250
40 FR	2900
10 DW	2800
25 DW	2380
30 DW	2240
40 DW	2000

Printed on 26/04/2024 22:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..