

## TR 882 - Spécifications techniques



### Description

TR 882 est un pneu polyvalent convenant à de nombreuses applications et machines. Il a été conçu pour les outils agricoles, les machines pour la récolte du foin/presses à paille et les engins pour les plantations de canne à sucre. Développé avec un mélange spécial pour réduire les dommages, ce pneu assure durabilité supérieure et traction excellente dans toutes les conditions dans les champs. TR 882 est aussi disponible dans les versions "aramid-belted", "HD" et "special" pour répondre aux exigences les plus spécifiques des utilisateurs finaux.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Presse à paille • Moissonneuse • Outillage agricole • Remorque  
Industriel: Remorque

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	132 A8
LI/SS FREE ROLLING	145 A8

## Dimensions US Standard

Usa code	94019861
Ply Rating	14
Section Width (inch)	15.7
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	14.9
Rolling Circumference (inch)	102.6
Rim Rec	AG 13.00
ECE	E4-106R-001879

## Load capacity (lbs)

mph / psi	52
5 FR	8950
15 FR	7610
20 FR	7160
25 FR	6390
5 DW	6170
15 DW	5250
20 DW	4940
25 DW	4410

Printed on 26/04/2024 18:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..