

TRAC FARM PLUS - Spécifications techniques



Description

TRAC FARM PLUS est un pneu arrière pour tracteurs spécialement conçu pour les applications de travail de la terre et de transport. Ce pneu se distingue de par une bande de roulement plus profonde avec pavés à deux angles afin de garantir tant une excellente traction qu'une conduite confortable sur la route. Le dessin spécial de la bande de roulement offre un contact plus large pour une meilleure stabilité et des propriétés d'auto-nettoyage extraordinaires. TRAC FARM PLUS allonge le cycle de vie du pneu.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	12.4 - 28
LI/SS	125 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	320
Overall Diameter (mm)	1295
Static Loaded Radius (mm)	603
Rolling Circumference (mm)	3899
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-004526
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.50
30	1650

Printed on 28/04/2024 01:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..