

## TRAC FARM PLUS - Spécifications techniques



### Description

TRAC FARM PLUS est un pneu arrière pour tracteurs spécialement conçu pour les applications de travail de la terre et de transport. Ce pneu se distingue de par une bande de roulement plus profonde avec pavés à deux angles afin de garantir tant une excellente traction qu'une conduite confortable sur la route. Le dessin spécial de la bande de roulement offre un contact plus large pour une meilleure stabilité et des propriétés d'auto-nettoyage extraordinaires. TRAC FARM PLUS allonge le cycle de vie du pneu.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	14.9 - 28
LI/SS	134 A6

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	390
Overall Diameter (mm)	1380
Static Loaded Radius (mm)	642
Rolling Circumference (mm)	4179
Rim Rec	W 13
Rim Alt	W 12 ; W 11
ECE	E11-106R-006811
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.30
30	2120

Printed on 27/04/2024 21:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..