

TRAC SUPER - Fiche de données



Description

Le pneu TRAC SUPER est la première taille radiale introduite par BKT dans le segment municipalité. La structure du pneu avec des ceintures en acier garantit une conduite stable associée à d'excellentes qualités de traction. Par conséquent il est tout particulièrement adapté aux applications sur les grandes surfaces herbeuses telles que les parcs et les bords de route.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Micro tracteur

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
400/50 R 15	STANDARD	118 A8/B	13.00		380	775	329	2269	370	TL	E11-106R-009073
440/50 R 17	STANDARD	135 D	14.00	13.00	441	872	395	2674	410	TL	E4-106R-000662
500/50 R 17	STANDARD	147 D	16.00		490	940			450	TL	E11-106R-007767

Printed on 26/04/2024 19:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..