

VIJETA - Spécifications techniques



Description

VIJETA est un pneu agricole qui convient pour les applications sur route et hors route. Le dessin de la bande de roulement avec nervure à 5 côtes optimise la répartition de la charge. De plus, le mélange résistant à l'usure et la carcasse robuste garantissent un long cycle de vie du pneu.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

Version	STANDARD
Type	TT
Tyre Size	6.00 - 19
LI/SS	105 A3

Dimensions US Standard

Usa code	94052356
Ply Rating	8
Section Width (inch)	6.9
Overall Diameter (inch)	31.9
Rim Rec	4.00

Load capacity (lbs)

	mph / psi	60
	10	2040

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/05/2025 15:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..