

XL GRIP (ADT) - Spécifications techniques



Description

Le XL GRIP (ADT) est un pneu à carcasse radiale pour camions à benne articulés conçus pour minimiser les coupures et les perforations dans des conditions particulièrement difficiles exigeant une traction exceptionnelle. Ces caractéristiques se traduisent par une durée de vie prolongée des pneus.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Tombereau articulé

Version	STANDARD
Type	TL
Tyre Size	26.5 - 25

Dimensions US Standard

Usa code	94057863
Ply Rating	28
Overall Width (inch)	26.8
Overall Diameter (inch)	68.5
Static Loaded Radius (inch)	31.3
Rolling Circumference (inch)	202.8
Rim Rec	22.00/3.0
TRA Code	E3

Load capacity (lbs)

mph / psi	51
30	22000

Printed on 25/04/2024 05:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..