

## XL GRIP (BHL) - Spécifications techniques



### Description

XL GRIP (BHL) a été particulièrement conçu pour les chargeuses pelleteuses utilisées dans les opérations pénibles lors des applications d'excavation, nivellement et chargement. Le dessin non directionnel de la bande de roulement assure d'excellentes traction et stabilité. Le mélange spécial de la bande de roulement confère une excellente résistance aux coupures et déchirures et allonge la vie du pneu.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriel: Chargeuse-pelleteuse

Version	STANDARD
Type	TT
Tyre Size	9.00 - 16
LI/SS	137 A6

## Dimensions US Standard

Usa code	94051106
Ply Rating	16
Section Width (inch)	10.2
Overall Diameter (inch)	35.8
Rim Rec	6.50 H
Rim Alt	6.00 G

## Load capacity (lbs)

mph / psi	105
20	5070

Printed on 25/04/2024 08:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..