

## XL GRIP (G3) - Spécifications techniques



### Description

XL GRIP (G-3) est un pneu à construction diagonale pour niveleuses, conçu pour réduire au minimum les risques de coupures et perforations dans les applications pénibles de nivelage, qui demandent une traction exceptionnelle.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Niveleuse

|           |            |
|-----------|------------|
| Version   | STANDARD   |
| Type      | TT         |
| Tyre Size | 14.00 - 24 |

## Dimensions US Standard

|                              |                              |
|------------------------------|------------------------------|
| Usa code                     | 94062959                     |
| Ply Rating                   | 16                           |
| Overall Width (inch)         | 14.4                         |
| Overall Diameter (inch)      | 53                           |
| Static Loaded Radius (inch)  | 24.3                         |
| Rolling Circumference (inch) | 157.6                        |
| Rim Rec                      | 8.00 TG SDC                  |
| Rim Alt                      | 9.00/1.5 (DC) ; 10.00/VA SDC |
| TRA Code                     | G3                           |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 51   |
| 25        | 8050 |

Printed on 23/04/2024 21:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..