

## XL GRIP (G3) - Spécifications techniques



### Description

XL GRIP (G-3) est un pneu à construction diagonale pour niveleuses, conçu pour réduire au minimum les risques de coupures et perforations dans les applications pénibles de nivelage, qui demandent une traction exceptionnelle.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Niveleuse

Version	STANDARD
Type	TL
Tyre Size	16.00 - 24 (-)

## Dimensions International Standard

Ply Rating	16
Overall Width (mm)	432
Overall Diameter (mm)	1450
Static Loaded Radius (mm)	654
Rolling Circumference (mm)	4289
SRI (mm)	-
Rim Rec	10.00 VA SDC
Rim Alt	-
TRA Code	G3

## Load capacity (Kg)

km/h / bar	3.00
40	4500

Printed on 23/04/2024 20:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..