

XL GRIP IND3 (ECH) - Spécifications techniques



Description

XL GRIP (IND-3) est un pneu à construction diagonale pour les applications d'empilement et de levage. Ce pneu est caractérisé par une carcasse robuste qui se traduit par une grande durabilité ainsi qu'une stabilité élevée lors des opérations de levage.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneurs vide

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94049035
Ply Rating	32
Overall Width (inch)	20.1
Overall Diameter (inch)	63.6
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	188.2
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND3

Load capacity (lbs)

mph / psi	131
5	44600
15	41300

Printed on 26/04/2024 05:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..