

XL GRIP (L3) - Spécifications techniques



Description

XL GRIP (E-3/L-3) est un pneu à construction diagonale à base large conçu pour les chargeuses afin de réduire au minimum les risques de coupures et perforations dans les applications difficiles de chargement. Ce pneu bénéficie d'une excellente traction ainsi que d'un cycle de vie plus long.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chargeur

OTR: Bulldozer • Chargeur

Version	STANDARD
Type	TL
Tyre Size	17.5 - 25

Dimensions International Standard

Ply Rating	12
Overall Width (mm)	435
Overall Diameter (mm)	1345
Static Loaded Radius (mm)	622
Rolling Circumference (mm)	3980
Rim Rec	14.00/1.5
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	2.25	3.50
50	3650	-
10	-	6150

Printed on 19/04/2024 04:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..