

XL GRIP (L3) - Fiche de données



Description

XL GRIP (E-3/L-3) est un pneu à construction diagonale à base large conçu pour les chargeuses afin de réduire au minimum les risques de coupures et perforations dans les applications difficiles de chargement. Ce pneu bénéficie d'une excellente traction ainsi que d'un cycle de vie plus long.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chargeur

OTR: Bulldozer • Chargeur

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
16.0/70 - 20	STANDARD	L3	16	13 SDC		405	1090	480	3295	TL
15.5 - 25	STANDARD	E3/L3	12	12.00/1.3	12.00/1.3 (DC)	402	1285	573	3767	TL
17.5 - 25	DUAL BEAD	E3/L3	20	14.00/1.5		435	1345	622	3980	TT
17.5 - 25	DUAL BEAD	E3/L3	24	14.00/1.5		435	1345	622	3980	TL
17.5 - 25	DUAL BEAD	E3/L3	20	14.00/1.5		435	1345	622	3980	TL
17.5 - 25	STANDARD	E3/L3	12	14.00/1.5		435	1345	622	3980	TL
17.5 - 25	STANDARD	E3/L3	16	14.00/1.5		435	1345	622	3980	TL
17.5 - 25	STANDARD	E3/L3	20	14.00/1.5		435	1345	622	3980	TL
20.5 - 25	STANDARD	E3/L3	12	17.00/2.0		530	1485	682	4395	TL
20.5 - 25	STANDARD	E3/L3	16	17.00/2.0		530	1485	682	4395	TL
20.5 - 25	STANDARD	E3/L3	20	17.00/2.0		530	1485	682	4395	TL
20.5 - 25	STANDARD	E3/L3	24	17.00/2.0		530	1485	682	4395	TL
23.5 - 25	ARAMID BELTED HD	E3/L3	24	19.50/2.5		600	1625	742	4810	TL
23.5 - 25	STANDARD	E3/L3	16	19.50/2.5		600	1625	742	4810	TL
23.5 - 25	STANDARD	E3/L3	20	19.50/2.5		600	1625	742	4810	TL
23.5 - 25	STANDARD	E3/L3	24	19.50/2.5		600	1625	742	4810	TL
26.5 - 25	STANDARD	L3	20	22.00/3.0		680	1740	796	5150	TL
26.5 - 25	STANDARD	L3	28	22.00/3.0		680	1740	796	5150	TL
26.5 - 25	STANDARD	L3	32	22.00/3.0		680	1740	796	5150	TL
29.5 - 25	STANDARD	L3	28	25.00/3.5		760	1860	849	5544	TL
29.5 - 25	STANDARD	L3	32	25.00/3.5		760	1860	849	5544	TL

Printed on 19/04/2024 03:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..