

## XL GRIP (T) - Spécifications techniques



### Description

XL GRIP (E-3) convient tout à fait pour les tombereaux automoteurs qui transportent des charges lourdes dans les applications de mine. Le mélange de la bande de roulement est conçu pour réduire au minimum les risques de coupures et perforations sur les terrains les plus difficiles. XL GRIP (E-3) offre une traction exceptionnelle, assurant ainsi un cycle de vie élevé du pneu.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Camion à benne basculante

Version	STANDARD
Type	TL
Tyre Size	12.00 - 24

## Dimensions US Standard

Usa code	94027590
Ply Rating	20
Overall Width (inch)	12.6
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	146.1
Rim Rec	8.5
Rim Alt	8.0
Tread Depth	30

## Load capacity (lbs)

mph / psi	115
50 LS/LD	8540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 15/01/2025 20:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..