

XL GRIP (T) - Spécifications techniques



Description

XL GRIP (E-3) convient tout à fait pour les tombereaux automoteurs qui transportent des charges lourdes dans les applications de mine. Le mélange de la bande de roulement est conçu pour réduire au minimum les risques de coupures et perforations sur les terrains les plus difficiles. XL GRIP (E-3) offre une traction exceptionnelle, assurant ainsi un cycle de vie élevé du pneu.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Camion à benne basculante

Version	STANDARD
Type	TT
Tyre Size	8.25 - 16

Dimensions International Standard

Ply Rating	16
Section Width (mm)	238
Overall Diameter (mm)	870
Rim Rec	6.50 H
Rim Alt	6.00 G
Tread Depth	20

Load capacity (Kg)

km/h / bar	8.20
50 LS	2070
50 LD	1960

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 15/01/2025 21:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..