

XL GRIP ULTRA - Spécifications techniques



Description

XL GRIP ULTRA est un pneu à construction diagonale conçu pour les tombereaux utilisés dans des conditions de service pénibles, telles que dans les applications minières, dans les carrières ou sur les chantiers. Le dessin non directionnel de la bande de roulement offre une excellente traction avant et latérale. Ce pneu est caractérisé par une carcasse robuste en nylon avec les joints de raccordement optimisés et par un mélange spécial de la bande de roulement pour assurer une extraordinaire résistance aux coupures et crevaisons, une excellente durabilité et résistance à l'usure ainsi que des propriétés élevées d'autonettoyage, même sur les surfaces rocheuses.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Camion à benne basculante

Version	CUT RESISTANT
Type	TT
Tyre Size	12.00 - 24

Dimensions US Standard

Usa code	94070916
Ply Rating	20
Overall Width (inch)	12.6
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	146.1
Rim Rec	8.5
Rim Alt	8.0
Tread Depth	30

Load capacity (lbs)

mph / psi	115
50 LS/LD	8540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/06/2025 20:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..