

AGRIMAX FORTIS - Technical Specifications



Description

AGRIMAX FORTIS is your reliable partner for all preparation, soil tillage and haulage operations. Designed to equip the latest, most modern and most powerful tractors, AGRIMAX FORTIS allows you to carry very high loads reaching up to 65 km/h (40 MPH). It ensures outstanding traction along with top handling and best comfort for a perfect driving experience. The tire has been designed with a reinforced nylon casing for enhanced productivity in the fields preserving the soil thanks to reduced compaction.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	600/70 R 34
LI/SS	160 D/163 A8

Dimensions International Standard

Section Width (mm)	591
Overall Diameter (mm)	1704
Static Loaded Radius (mm)	761
Rolling Circumference (mm)	5109
SRI (mm)	800
Rim Rec	DW 18 L
Rim Alt	DW 20 B ; W 18 L
ECE	E4-106R-001401
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2160	2520	2835	3150	3465	3735	4140	4500
50	2270	2650	2980	3310	3640	3925	4350	4725
40	2340	2730	3075	3415	3755	4050	4485	4875
30	2485	2900	3265	3625	3985	4300	4765	5175
10 LT	2895	3380	3800	4225	4645	5005	5550	6030
10 HT	2485	2900	3265	3625	3985	4300	4765	5175

Printed on 05/05/2024 13:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..