

AGRIMAX RT 600 - Technical Specifications

Description

AGRIMAX RT 600 is the ideal tire for grassland, harvesting and spreading applications. Thanks to its large contact area, AGRIMAX RT 600 ensures an excellent pressure distribution on the land reducing damage on grassland and protecting your soil. Thanks to its round shoulder technology, the reinforced bead and increased number of lugs, it guarantees great stability and traction.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Harvester • Spreader • Tractor



Version	STANDARD
Type	TL
Tyre Size	620/75 R 26 (23.1 R 26)
LI/SS	167 A8/B

Dimensions International Standard

Section Width (mm)	625
Overall Diameter (mm)	1590
Static Loaded Radius (mm)	730
Rolling Circumference (mm)	4851
SRI (mm)	750
Rim Rec	DW 20 B
ECE	E11-106R-002993

Load capacity (Kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	2510	2890	3545	3870	4255	4635	5015	5450	-	-
40	2510	2890	3545	3870	4255	4635	5015	5450	-	-
30	2685	3095	3795	4145	4555	4960	5370	5835	-	-
10 LT	3365	3875	4750	5190	5700	6210	6725	7305	-	-
10 HT	2685	3095	3795	4145	4555	4960	5370	5835	-	-
10 Cyc.	-	4125	5285	5795	6720	7370	8065	8760	8895	9265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 03/05/2025 12:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..