

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	320/65 R 18
LI/SS	125 A8/B

Dimensions US Standard

Usa code	94073252
Section Width (inch)	12.2
Overall Diameter (inch)	34.8
Static Loaded Radius (inch)	15.7
Rolling Circumference (inch)	105
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E11-106R-008145
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	47
30	1200	1420	1640	1820	2040	2230	2660	2950	3320	3640
25	1200	1420	1640	1820	2040	2230	2660	2950	3320	3640
20	1290	1530	1760	1950	2190	2380	2850	3160	3560	3900
5 LT	1620	1910	2200	2450	2740	2990	3570	3960	4450	4880
5 HT	1290	1530	1760	1950	2190	2380	2850	3160	3560	3900

Printed on 01/03/2024 05:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..