

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	340/65 R 20
LI/SS	124 D/127 A8

Dimensions International Standard

Section Width (mm)	343
Overall Diameter (mm)	950
Static Loaded Radius (mm)	430
Rolling Circumference (mm)	2892
SRI (mm)	450
Rim Rec	W 11
Rim Alt	W 10 ; W 12
ECE	E4-106R-001413
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	755	880	1010	1120	1235	1330	1475	1600
50	790	925	1060	1180	1295	1395	1550	1680
40	825	965	1105	1225	1350	1455	1610	1750
30	865	1015	1160	1290	1420	1530	1695	1840
10 LT	1010	1180	1355	1505	1655	1785	1975	2145
10 HT	865	1015	1160	1290	1420	1530	1695	1840

Printed on 02/03/2024 17:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..