

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	440/65 R 28
LI/SS	138 D/141 A8

Dimensions International Standard

Section Width (mm)	441
Overall Diameter (mm)	1283
Static Loaded Radius (mm)	590
Rolling Circumference (mm)	3927
SRI (mm)	625
Rim Rec	W 14 L
Rim Alt	W 13 ; W 15 L
ECE	E4-106R-000767
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1135	1325	1490	1655	1820	1960	2175	2360
50	1195	1390	1565	1740	1910	2060	2285	2480
40	1240	1445	1625	1805	1985	2140	2370	2575
30	1305	1525	1715	1905	2095	2255	2500	2715
10 LT	1520	1775	1995	2220	2440	2630	2915	3165
10 HT	1305	1525	1715	1905	2095	2255	2500	2715

Printed on 26/04/2024 22:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..