

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	540/65 R 24
LI/SS	146 D/149 A8

Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	1312
Static Loaded Radius (mm)	590
Rolling Circumference (mm)	3930
SRI (mm)	625
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E4-106R-000773
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1440	1680	1890	2100	2310	2490	2760	3000
50	1515	1765	1985	2205	2430	2615	2900	3150
40	1560	1820	2050	2275	2505	2700	2990	3250
30	1660	1935	2175	2415	2660	2865	3175	3450
10 LT	1930	2255	2535	2815	3100	3340	3700	4020
10 HT	1660	1935	2175	2415	2660	2865	3175	3450

Printed on 03/03/2024 02:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..