

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	240/70 R 16
LI/SS	104 A8/B

Dimensions International Standard

Section Width (mm)	244
Overall Diameter (mm)	742
Static Loaded Radius (mm)	335
Rolling Circumference (mm)	2176
SRI (mm)	350
Rim Rec	W 8
Rim Alt	W 8 L ; W 9 L
ECE	E4-106R-000609
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	425	490	560	630	705	775	840	900
40	425	490	560	630	705	775	840	900
30	455	525	600	680	755	830	900	965
10 LT	570	655	755	850	945	1045	1130	1210
10 HT	455	525	600	680	755	830	900	965

Printed on 23/04/2024 08:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..