

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	280/70 R 18
LI/SS	114 A8/B

Dimensions US Standard

Usa code	94021901
Section Width (inch)	11.1
Overall Diameter (inch)	33.4
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	100.3
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000635
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	1220	1410	1620	1830	2040	2240	2420	2600
25	1220	1410	1620	1830	2040	2240	2420	2600
20	1310	1510	1730	1960	2180	2400	2600	2790
5 LT	1640	1900	2170	2450	2730	3010	3250	3490
5 HT	1310	1510	1730	1960	2180	2400	2600	2790

Printed on 26/04/2024 14:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..