

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	480/70 R 34
LI/SS	149 D

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1580
Static Loaded Radius (mm)	711
Rolling Circumference (mm)	4772
SRI (mm)	750
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-005524
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1530	1755	2015	2275	2535	2795	3055	3250
50	1610	1845	2120	2395	2665	2940	3215	3415
40	1675	1925	2210	2495	2780	3065	3350	3560
30	1760	2020	2320	2620	2920	3220	3520	3740
10 LT	2050	2355	2705	3050	3400	3750	4095	4355
10 HT	1760	2020	2320	2620	2920	3220	3520	3740

Printed on 23/04/2024 16:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..