

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STEEL BELTED
Type	TL
Tyre Size	580/70 R 38
LI/SS	180 D

Dimensions International Standard

Section Width (mm)	577
Overall Diameter (mm)	1827
Static Loaded Radius (mm)	821
Rolling Circumference (mm)	5505
SRI (mm)	850
Rim Rec	W 18 L
Rim Alt	DW 18 L ; DD 18 L
ECE	E11-106R-005836
TRA Code	R1W

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4	4.6
65	3180	3875	4930	5480	6000	6470	6930	7370	7790	8000
50	3340	4070	5180	5755	6300	6795	7280	7740	8180	8400
40	3485	4245	5400	6005	6570	7085	7590	8075	8535	8760
30	3660	4460	5670	6305	6900	7445	7970	8480	8960	9200
25	3770	4595	5845	6495	7110	7670	8215	8735	9235	9480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 06:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..