

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	650/75 R 38
LI/SS	169 D

Dimensions US Standard

Usa code	94063895
Section Width (inch)	25.8
Overall Diameter (inch)	76.4
Static Loaded Radius (inch)	34.4
Rolling Circumference (inch)	229.1
Rim Rec	DW 21 B
Rim Alt	DW 20 B ; DW 23 B
ECE	E11-106R-006161
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	6020	6910	7940	8950	9980	11000	12030	12790
30	6320	7250	8330	9400	10480	11550	12620	13430
25	6590	7570	8700	9810	10930	12060	13170	14010
15	6910	7950	9130	10300	11470	12650	13820	14700
5 LT	8060	9260	10640	12000	13370	14750	16110	17140
5 HT	6910	7950	9130	10300	11470	12650	13820	14700

Printed on 20/04/2024 17:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..