



## AGRIMAX RT 765 - Data Sheet



### Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	TKPH	ECE
200/70 R 16	STANDARD	R1W	94 A8/B	W 6		197	686	315	2060	330	TL		E4-106R-000607
220/70 R 16	STANDARD	R1W	99 A8/B	W 7	W 8	221	715	324	2145	340	TL		E11-106R-003354
240/70 R 16	STANDARD	R1W	104 A8/B	W 8	W 8 L ; W 9 L	244	742	335	2176	350	TL		E4-106R-000609
260/70 R 16	STANDARD	R1W	109 A8/B	W 8	W 8 L ; W 9 L	258	770	346	2283	360	TL		E4-106R-000610
280/70 R 16	STANDARD	R1W	112 A8/B	W 9	W 8 ; W 8 L ; W 10	282	798	356	2370	390	TL		E4-106R-000633
280/70 R 18	STANDARD	R1W	114 A8/B	W 9	W 8 ; W 10	282	849	381	2547	410	TL		E4-106R-000635
260/70 R 20	SPECIAL	R1W	113 A8/B	W 8	9 ; W 9	258	872	402	2639	410	TL		E4-106R-000640
260/70 R 20	STANDARD	R1W	113 A8/B	W 8	9 ; W 9	258	872	402	2639	425	TL		E4-106R-000640
280/70 R 20	SPECIAL	R1W	116 A8/B	W 9	W 8 ; W 10	282	900	408	2705	450	TL		E4-106R-00641
280/70 R 20	STANDARD	R1W	116 A8/B	W 9	W 8 ; W 10	282	900	408	2705	450	TL		E4-106R-00641
300/70 R 20	STANDARD	R1W	120 A8/B	W 9	W 10	295	952	428	2854	450	TL		E4-106R-000643
320/70 R 20	STANDARD	R1W	123 A8/B	W 10	W 9 ; W 11	319	982	445	2938	450	TL		E4-106R-000644
360/70 R 20	STANDARD	R1W	129 A8/B	W 11	W 10 ; W 12	357	1042	469	3122	475	TL		E4-106R-000647
380/70 R 20	STANDARD	R1W	132 A8/B	W 12	W 11 ; W 13	380	1082	482	3213	500	TL		E4-106R-00648
320/70 R 24	SPECIAL	R1W	116 D	W 10	W 9 ; W 11	319	1094	502	3245	525	TL		E11-106R-005827
320/70 R 24	STANDARD	R1W	116 D	W 10	W 9 ; W 11	319	1094	502	3245	525	TL		E11-106R-005827
360/70 R 24	SPECIAL	R1W	122 D	W 11	W 10 ; W 12	357	1152	519	3395	550	TL	1	E11-106R-005824
360/70 R24	STANDARD	R1W	122 D	W 11	W 10 ; W 12	357	1152	519	3395	550	TL		E11-106R-005824
380/70 R 24	SPECIAL	R1W	125 D	W 12	W 11 ; W 13	380	1190	538	3560	550	TL	1	E11-106R-005767
380/70 R 24	STANDARD	R1W	125 D	W 12	W 11 ; W 13	380	1190	538	3560	550	TL		E11-106R-005767
420/70 R 24	SPECIAL	R1W	130 D	W 13	W 12 ; W 14 L	418	1248	554	3680	575	TL		E11-106R-005826
420/70 R 24	SPECIAL	R1W	134 D	W 13	W 12 ; W 14 L	418	1248	554	3680	575	TL	1	E11-106R-005825
420/70 R 24	STANDARD	R1W	130 D	W 13	W 12 ; W 14 L	418	1248	554	3680	575	TL		E11-106R-005826
420/70 R 24	STANDARD	R1W	134 D	W 13	W 12 ; W 14 L	418	1248	554	3680	575	TL		E11-106R-005825
480/70 R 24	SPECIAL	R1W	138 D	W 15 L	W 14 L ; W 16 L	479	1316	580	3894	600	TL		E11-106R-005519
480/70 R 24	STANDARD	R1W	138 D	W 15 L	W 14 L ; W 16 L	479	1316	580	3894	600	TL		E11-106R-005519
360/70 R 28	SPECIAL	R1W	125 D	W 11	W 10 ; W 12	357	1251	579	3767	600	TL		E11-106R-005828
360/70 R 28	STANDARD	R1W	125 D	W 11	W 10 ; W 12	357	1251	579	3767	600	TL		E11-106R-005828
380/70 R 28	SPECIAL	R1W	127 D	W 12	W 11 ; W 13	380	1293	586	3883	600	TL		E11-106R-005829
380/70 R	STANDARD	R1W	127 D	W 12	W 11 ; W 13	380	1293	586	3883	600	TL		E11-106R-

<b>28</b>												005829
<b>420/70 R 28</b>	SPECIAL	R1W	133 D	W 13	W 12 ; W 14 L	418	1349	604	4020	625	TL	E11-106R-005520
<b>420/70 R 28</b>	STANDARD	R1W	133 D	W 13	W 12 ; W 14 L	418	1349	604	4020	625	TL	E11-106R-005520
<b>480/70 R 28</b>	SPECIAL	R1W	140 D	W 15 L	W 14 L ; W 16 L	479	1421	634	4185	650	TL	E11-106R-005521
<b>480/70 R 28</b>	STANDARD	R1W	140 D	W 15 L	W 14 L ; W 16 L	479	1421	634	4185	650	TL	E11-106R-005521
<b>600/70 R 28</b>	STANDARD	R1W	157 D	DW 18 L	DW 20 B	591	1551	696	4692	725	TL	E11-106R-006861
<b>420/70 R 30</b>	SPECIAL	R1W	134 D	W 13	W 12 ; W 14 L	418	1398	631	4172	650	TL	E11-106R-005830
<b>420/70 R 30</b>	STANDARD	R1W	134 D	W 13	W 12 ; W 14 L	418	1398	631	4172	650	TL	E11-106R-005830
<b>480/70 R 30</b>	SPECIAL	R1W	141 D	W 15 L	W 14 L ; W 16 L	479	1478	659	4372	675	TL	E11-106R-005522
<b>480/70 R 30</b>	STANDARD	R1W	141 D	W 15 L	W 14 L ; W 16 L	479	1478	659	4372	675	TL	E11-106R-005522
<b>600/70 R 30</b>	SPECIAL	R1W	152 D	DW 20 B	DW 18 L ; W 18 L	611	1602	711	4774	750	TL	E11-106R-005523
<b>600/70 R 30</b>	STANDARD	R1W	152 D	DW 20 B	DW 18 L ; W 18 L	611	1602	711	4774	750	TL	E11-106R-005523
<b>480/70 R 34</b>	SPECIAL	R1W	149 D	W 15 L	W 14 L ; W 16 L	479	1580	711	4772	750	TL	E11-106R-005524
<b>480/70 R 34</b>	SPECIAL	R1W	155 D	W 15 L	W 14 L ; W 16 L	479	1580	728	4788	750	TL	E11-106R-005834
<b>480/70 R 34</b>	STANDARD	R1W	149 D	W 15 L	W 14 L ; W 16 L	479	1580	711	4772	750	TL	E11-106R-005524
<b>480/70 R 34</b>	STANDARD	R1W	155 D	W 15 L	W 14 L ; W 16 L	479	1580	728	4788	750	TL	E11-106R-005834
<b>520/70 R 34</b>	SPECIAL	R1W	148 D	W 16 L	W 15 L ; W 18 L	516	1640	739	4927	775	TL	E11-106R-005831
<b>520/70 R 34</b>	STANDARD	R1W	148 D	W 16 L	W 15 L ; W 18 L	516	1640	739	4927	775	TL	E11-106R-005831
<b>480/70 R 38</b>	SPECIAL	R1W	145 D	W 15 L	W 14 L ; W 16 L	479	1681	764	5055	800	TL	E11-106R-005832
<b>480/70 R 38</b>	STANDARD	R1W	145 D	W 15 L	W 14 L ; W 16 L	479	1681	764	5055	800	TL	E11-106R-005832
<b>520/70 R 38</b>	SPECIAL	R1W	150 D	W 16 L	W 15 L ; W 18 L	516	1749	793	5300	825	TL	E11-106R-005525
<b>520/70 R 38</b>	STANDARD	R1W	150 D	W 16 L	W 15 L ; W 18 L	516	1749	793	5300	825	TL	E11-106R-005525
<b>580/70 R 38</b>	SPECIAL	R1W	155 D	W 18 L		577	1827	821	5471	850	TL	E11-106R-005526
<b>580/70 R 38</b>	STANDARD	R1W	155 D	W 18 L		577	1827	821	5471	850	TL	E11-106R-005526
<b>580/70 R 38</b>	STEEL BELTED	R1W	180 A8	W 18 L		577	1827	821	5505	850	TL	E4-106R-000809
<b>580/70 R 38</b>	STEEL BELTED	R1W	180 D	W 18 L		577	1827	821	5505	850	TL	E11-106R-005836
<b>620/70 R 38</b>	SPECIAL	R1W	170 D	DW 20 B	DW 18 L ; W 18 L	625	1833	828	5591	875	TL	E11-106R-005997
<b>620/70 R 38</b>	STANDARD	R1W	170 D	DW 20 B	DW 18 L ; W 18 L	625	1833	828	5591	875	TL	E11-106R-005997
<b>650/75 R 38</b>	STANDARD	R1W	169 D	DW 21 B	DW 20 B ; DW 23 B	655	1941	874	5820	925	TL	E11-106R-006161
<b>710/70 R 38</b>	SPECIAL	R1W	175 D/178 A8	DW 23 B		716	1959	859	5751	925	TL	E11-106R-006000
<b>710/70 R 38</b>	SPECIAL	R1W	166 D	DW 23 B		716	1959	859	5751	925	TL	E11-106R-005837
<b>710/70 R 38</b>	STANDARD	R1W	175 D/178 A8	DW 23 B		716	1959	859	5751	925	TL	E11-106R-006000

<b>710/70 R 38</b>	STANDARD	R1W	166 D	DW 23 B		716	1959	859	5751	925	TL		E11-106R-005837
<b>710/70 R 38</b>	STANDARD	R1W	171D/174A8	DW 23 B		716	1959	859	5751	925	TL		E11-106R-004072
<b>620/70 R 42</b>	SPECIAL	R1W	173 D	DW 20 B	DW 18 L	625	1935	876	5804	925	TL		E11-106R-005833
<b>620/70 R 42</b>	SPECIAL	R1W	160 D	DW 20 B	DW 18 L	625	1935	876	5742	925	TL		E11-106R-005835
<b>620/70 R 42</b>	SPECIAL	R1W	166 D	DW 20 B	DW 18 L	625	1935	876	5801	925	TL		E11-106R-005998
<b>620/70 R 42</b>	STANDARD	R1W	173 D	DW 20 B	DW 18 L	625	1935	876	5804	925	TL		E11-106R-005833
<b>620/70 R 42</b>	STANDARD	R1W	160 D	DW 20 B	DW 18 L	625	1935	876	5742	925	TL		E11-106R-005835
<b>620/70 R 42</b>	STANDARD	R1W	166 D	DW 20 B	DW 18 L	625	1935	876	5801	925	TL		E11-106R-005998
<b>650/75 R 42</b>	STANDARD	R1W	170 D	DW21B	DW20B;DW23B	655	2043	916	6147	975	TL		E11-106R-006402
<b>710/70 R 42</b>	SPECIAL	R1W	176 D/179 A8	DW 23 B	DW 25 B	716	2061	922	6174	975	TL	1	E11-106R-006001
<b>710/70 R 42</b>	STANDARD	R1W	176 D/179 A8	DW 23 B	DW 25 B	716	2061	922	6174	975	TL		E11-106R-006001
<b>710/70 R 42</b>	STANDARD	R1W	173 D/176 A8	DW 23 B	DW 25 B	716	2061	922	6174	975	TL		E4-106R-000807
<b>620/70 R 46</b>	SPECIAL	R1W	162 D	DW 20 B		625	2036	924	6106	975	TL	1	E11-106R-005999
<b>620/70 R 46</b>	STANDARD	R1W	162 D	DW 20 B		625	2036	924	6106	975	TL		E11-106R-005999

Printed on 23/04/2024 15:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..