

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	320/85 R 36
LI/SS	147 D/150 A8

Dimensions US Standard

Usa code	94052691
Section Width (inch)	13
Overall Diameter (inch)	57.4
Static Loaded Radius (inch)	26.5
Rolling Circumference (inch)	173.4
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-003511
TRA Code	R1W

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58	64
45	2560	2930	3310	3990	4430	4670	5110	5540	5920	6230	6780
30	2690	3090	3470	4200	4650	4920	5380	5830	6230	6550	7120
25	2800	3210	3630	4380	4850	5130	5600	6070	6490	6820	7390
20	2940	3370	3800	4590	5090	5380	5870	6380	6810	7160	7800
5 LT	3430	3940	4430	5360	5940	6270	6860	7440	7950	8360	9090
5 HT	2940	3370	3800	4590	5090	5380	5870	6380	6810	7160	7800

Printed on 26/04/2024 05:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..