

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	460/85 R 34 (18.4 R 34)
LI/SS	158 A8/B

Dimensions International Standard

Section Width (mm)	475
Overall Diameter (mm)	1646
Static Loaded Radius (mm)	721
Rolling Circumference (mm)	4865
SRI (mm)	775
Rim Rec	W 16 L
Rim Alt	W 14 L ; W 15 L
ECE	E11-106R-006759
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	1660	1955	2255	2510	2805	3060	3360	3615	3955	4250
40	1660	1955	2255	2510	2805	3060	3360	3615	3955	4250
30	1755	2095	2415	2685	3005	3280	3595	3870	4235	4550
10 LT	2225	2620	3020	3365	3760	4105	4500	4845	5300	5695
10 HT	1900	2245	2585	2875	3215	3510	3850	4140	4530	4870

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 03:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..