

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction



Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	460/85 R 34 (18.4 R 34)
LI/SS	158 A8/B

Dimensions US Standard

Usa code	94047772
Section Width (inch)	18.7
Overall Diameter (inch)	64.8
Static Loaded Radius (inch)	28.4
Rolling Circumference (inch)	191.5
Rim Rec	W 16 L
Rim Alt	W 14 L ; W 15 L
ECE	E11-106R-006759
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
30	3660	4310	4970	5530	6180	6750	7410	7970	8720	9370
25	3660	4310	4970	5530	6180	6750	7410	7970	8720	9370
20	3910	4620	5320	5920	6620	7230	7930	8530	9340	10030
5 LT	4910	5780	6660	7420	8290	9050	9920	10680	11680	12550
5 HT	4190	4950	5700	6340	7090	7740	8490	9130	9990	10740

Printed on 25/04/2024 04:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..